



Sweeper 2 in 1 (SCC)	132
Pickup Sweeper (BRB)	134
High Pressure Cleaner (VHPC)	136







SWEEPER 2 IN 1



- Simple and efficient solution for all light and medium duty sweeping applications.
- Ø 520mm polyethilen brush.
- 2 in 1: sweeper-collector and side-pushing sweeper.
- Full hydraulic protection; no hydraulic backline required.
- Version "HWA +" equipped with an electric spraying system (120L).
- Recommended options: continuous hydraulic flow & hand throttle (when available).
- Side brush available from spare part department only: left (ref. 52000520) or right (ref. 52000597).





Paralelogram mounted- perfect adaptation to road profile



Optional side brush Ø 320mm



Version "+": reinforced wheels Ø 320mm

* No compatibility with MT-X version

	SCC 2050	SCC 2600	SCC 2050 +	SCC 2600 +	SCC 2050 HWA +	SCC 2600 HWA +
Capacity (I)	200	250	200	250	200	250
Width (mm)	2050	2600	2050	2600	2050	2600
Diameter (mm)	520	520	520	520	520	520
Weight (kg)	380	450	385	455	480	500
Water sprayer and hydraulic swivel	No	No	No	No	Yes	Yes

Machine compatibil	ity					
Reference	52000514	52000515	52000516	52000517	52000518	52000519
MLT 625	Х		X		X	
MLT 630 News		Χ		Χ		Χ
MLT 635 New 16		X		X		Χ
MLT 730 New 46		X		X		Х
MLT 733 New 46		Χ		Χ		Х
MLT-X 735		X		X		Χ
MLT 737 New 46		Х		Χ		Х
MLT 741 New 46		X		X		Χ
MLT 840		Х		X		Х
MLT 940 New 46		X		X		Χ
MLT 1040		X		X		Χ
MLA-T 533		X		X		Χ
MT 420	Х		X		X	
MT 625	Χ		X		Χ	
MT 733 Easy *		X		Χ		Х
MT 933 Easy *		X		X		Χ
MT 1135		Х		Χ		Χ
MT 1335		Х		X		Х







PICKUP SWEEPER



- Perfect sweeper for intensive/ demanding applications
- Sweep and pick-up in one operation.
- Up to 2500m² cleaned in 10 minutes.
- High quality sweeping.
- Recommended hand throttle & continuous hydraulic flow options.





Polyester & steel brush for perfect sweeping along walls or side walks



Interchangeable side brush (left or right)



Swivel wheels for an easy driving process

	BRB 1600	BRB 2200	BRB 2500
Capacity (kg)	380	530	600
Width (mm)	2000	2600	2900
Weight (kg)	775	925	1000

Machine compatibility				
Reference	790313	790315	790316	
MLT 625	X			
MLT 635 New 16		X		
MLT-X 735		X		
MLT 737 New 16		Х		
MLT 741 New 16		Х		
MLT 840		Х		
MLT 940 New 16		Х		
MLT 961		Х	Х	
MT 625	X			







HIGH PRESSURE CLEANER



- High pressure cleaning in total autonomy- no need for electricity or water supply.
- 45 minutes of autonomy at 200 bar.
- Pressure regulation system (10 to 200 bar).
- Manometer as standard.
- Recommended options: continuous hydraulic flow & hand throttle (when available).





Easy to hitch on standard forks



Nozzle spray for powerful and accurate cleaning



40 meter hose reel

	VHPC 600
Capacity (L)	600
Width (mm)	1451
Height (mm)	1520
Weight (kg)	240

Machine compatibility	
Reference	790335
MLT 625	Х
MLT 630 New46	X
MLT 730 New46	X
MLT-X 735	X
MLT 737 New46	X
MLT 741 New46	X
MLT 840	X
MLT 940 New 16	X
MLT 1040	X

MANDATORY MACHINE EQUIPMENT: | + | + | ...



E-Reco, an attachment recognition system for greater simplicity

Manitou is offering, as standard, the attachment-recognition system on its new-generation of rotary telescopic trucks MRT EASY and MRT PRIVILEGE +.

The system uses RFID radio-identification technology, very widely used in industry and retail.

This autonomous technique can remotely recover and record data. The machine detects the attachment at the head of the boom, analyses its data and directly proposes the corresponding working configuration (working envelope + movement speed + safety).

This technology provides the load chart in real time, taking into account the rotation angle of the turret and the position of the machine's stabilisers and in accordance with the mobile crane standard.

TABLE SYMBOL

*	No predisposition required
88	Hydraulic line
	Return piping to hydraulic oil tank
	Electric predisposition
	Platform predisposition
	Tyre handler, cylinder handler predisposition
Co.	Please contact your Manitou subsidiary (special solution request required)
	Round bale
rent.	Square bale
	Wrapped bale
	Suspended load : read user manual
E-RECD RECOGNITION CONTROL	Machine equipped with attachment recognition system





