


Technical sheet

# MSI 25

Masted Forklift Trucks



	Technical characteristics	Metric
1.1	Manufacturer	Manitou
1.2	Model	MSI 25
1.3	Type of traction	Diesel
1.4	Type of operation	Seated
1.5	Q - Rated capacity	2500 kg
1.8	x - Distance from the load bearing surface to the centre of the front axle	625 mm
1.9	y - Wheelbase	1800 mm
	<b>Weight</b>	
2.1	Weight of truck in working order	4070 kg
2.2	Laden weight on front/rear axle	5695 kg / 875 kg
2.3	Unladen weight on front/rear axle	1630 kg / 2440 kg
	<b>Wheels</b>	
3.5	Number of front wheels (x)	2x / 2
	<b>Dimensions</b>	
4.2	h1 - Height (mast lowered)	2300 mm
4.3	h2 - Free lift	130 mm
4.5	h4 - Height of extended mast	4131 mm
4.19	l1 - Total length	4045 mm
4.20	l2 - Length to fork heel	2950 mm
4.21	b1 - Overall width - Single/twin wheels	1320 mm / -
4.22	e / s / l - Fork dimensions	1100 x 100 x 40
4.23	Fork carriage to DIN 15173 A/B	FEM 2A
4.24	b3 - Width of fork clamp	1260 mm
4.33	Ast - Aisle width for 1000 x 1200 pallet widthwise	4530 mm
4.34	Ast - Aisle width for 800 x 1200 pallet lengthwise	4630 mm
4.35	Wa - Turning radius	2600 mm
	<b>Performances</b>	
5.1	Speed of travel laden / unladen	20 km/h / 20 km/h
5.5	Nominal pulling force laden / unladen	1860 daN / -
5.7	Maximum ramp laden / unladen	31 % / -
5.10	Service brake	Hydraulic
	<b>Engine</b>	
7.1	Engine manufacturer / Type	Kubota - V2403 ME3 / Stage 3A
7.2	Useful power	36 kW
7.4	Number of pistons / Capacity	4 / 2434 cm <sup>3</sup>
	<b>Miscellaneous</b>	
8.2	Working hydraulic pressure for attachments	170 bar
8.3	Oil flow rate for attachments	77 l/min



### Characteristics of masts and residual capacities

Duplex Total Visibility		FVD 27	FVD 30	FVD 33	FVD 35	FVD 37	FVD 40	FVD 45	FVD 50
Lift height	mm	2700	3000	3300	3500	3700	4000	4500	5000
Height (mast lowered)	mm	2000	2150	2300	2400	2560	2750	3000	3250
Free lift	mm	130	130	130	130	130	130	130	130
Height of extended mast	mm	3531	3831	4131	4331	4531	4831	5331	5831
Forward/backward mast tilt angle	°	10 / 12	10 / 12	10 / 12	10 / 12	10 / 12	10 / 12	10 / 12	6 / 6

Triplex Free Lift		FLT 37	FLT 40	FLT 43	FLT 47	FLT 50	FLT 55	FLT 60
Lift height	mm	3700	4000	4300	4700	5000	5500	6000
Height (mast lowered)	mm	1950	2050	2150	2300	2400	2560	2750
Free lift	mm	1221	1321	1421	1571	1671	1831	2021
Height of extended mast	mm	4469	4769	5069	5469	5769	6269	6769
Forward/backward mast tilt angle	°	10 / 12	10 / 12	10 / 12	10 / 12	6 / 6	6 / 6	6 / 6



Siège Social  
430 rue de l'Aubinière - 44150 Ancenis Cedex - France  
Tel: +33(0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97  
[www.manitou.com](http://www.manitou.com)



This brochure describes versions and configuration options for Manitou products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Manitou reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Manitou dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Manitou and may not be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,547,824 euros - 857 802 508 RCS Nantes