


Technical sheet

MSI 40

Masted Forklift Trucks



	Technical characteristics	Metric
1.1	Manufacturer	Manitou
1.2	Model	MSI 40
1.3	Type of traction	Diesel
1.5	Q - Rated capacity	4000 kg
1.8	x - Distance from the load bearing surface to the centre of the front axle	691 mm
1.9	y - Wheelbase	2075 mm
	Weight	
2.1	Weight of truck in working order	6980 kg
2.2	Laden weight on front/rear axle	9245 kg / 1735 kg
2.3	Unladen weight on front/rear axle	3210 kg / 3770 kg
	Wheels	
3.1	Tyre equipment: bandage (V), PPS (SE), inflatable tyre (L)	L
3.5	Number of front wheels (x)	2x / 2
	Dimensions	
4.2	h1 - Height (mast lowered)	2780 mm
4.5	h4 - Height of extended mast	4677 mm
4.19	l1 - Total length	4494 mm
4.20	l2 - Length to fork heel	3290 mm
4.21	b1 - Overall width - Single/twinned wheels	1730 mm / -
4.23	Fork carriage to DIN 15173 A/B	FEM 3A
4.24	b3 - Width of fork clamp	1670 mm
4.33	Ast - Aisle width for 1000 x 1200 pallet widthwise	4760 mm
4.34	Ast - Aisle width for 800 x 1200 pallet lengthwise	4900 mm
4.35	Wa - Turning radius	2870 mm
	Performances	
5.1	Speed of travel laden / unladen	22 km/h / 22 km/h
5.5	Nominal pulling force laden / unladen	3180 daN / -
5.7	Maximum ramp laden / unladen	24 % / 29 %
5.10	Service brake	Hydraulic
	Engine	
7.1	Engine manufacturer / Type	Perkins - 854 F 10794 / Stage 3B
7.2	Useful power	55 kW
7.4	Number of pistons / Capacity	4 / 3400 cm ³
	Miscellaneous	
8.2	Working hydraulic pressure for attachments	230 bar
8.3	Oil flow rate for attachments	103 l/min
8.4	Measured/guaranteed mean noise level at the ear of the operator	81 dB(A)



Characteristics of masts and residual capacities

Duplex Total Visibility		FVD 30	FVD 33	FVD 35	FVD 37	FVD 40	FVD 45	FVD 50
Lift height	mm	3000	3300	3500	3700	4000	4500	5000
Height (mast lowered)	mm	2425	2575	2675	2775	2925	3175	3425
Height of extended mast	mm	3977	4277	4477	4677	4977	5477	5977

Triplex Free Lift		FLT 37	FLT 40	FLT 43	FLT 45	FLT 47	FLT 50	FLT 55	FLT 60
Lift height	mm	3700	4000	4300	4500	4700	5000	5500	6000
Height (mast lowered)	mm	2175	2275	2375	2450	2510	2625	2775	2950
Free lift	mm	1258	1358	1458	1533	1593	1708	1858	2033
Height of extended mast	mm	4667	4967	5267	5467	5667	5967	6467	6967



Siège Social
430 rue de l'Aubinière - 44150 Ancenis Cedex - France
Tel: +33(0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97
www.manitou.com



This brochure describes versions and configuration options for Manitou products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Manitou reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Manitou dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Manitou and may not be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,547,824 euros - 857 802 508 RCS Nantes